



### Specification

<b>General</b>	
Monitor Dimensions	Width: 254.8mm Height: 177.5mm Depth: 40mm
LCD Type	10.1" IPS LED
Video Input	VGA and HDMI
OSD controls	Allow on-screen adjustments of Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Power Supply	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max
Mount Interface	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical
<b>LCD Specification</b>	
Active Area(mm)	216.96 (H) x 135.6(V)
Resolution	1280×800 @60Hz
Dot Pitch(mm)	0.1695(H) x 0.1695(V)
Nominal Input Voltage	+4V(Max)
Viewing angle (v/h)	89°/89°(CR>10)
Contrast	800:1
Luminance(cd/m2)	350
Response Time(Rising)	25msec
Support Color	16.7M colors
Backlight MTBF(hr)	10000(Min)
<b>External AC Power Adapter</b>	
Output	DC 12V /2A
Input	100-240 VAC, 50-60 Hz
MTBF	50000 hr at 25°C
<b>Environment</b>	
Operating Temp.	0~50°C
Storage Temp.	-20~60°C
Operating RH:	20%~80%
Storage RH:	10%~90%

**Components**  
 VGA Cable 180cm\*1 Pcs,  
 Power Cord with Switching Adapter \*1 Pcs,  
 Stand\*1 Pcs

**Remark:**  
 1. Trade Term: EXW Shenzhen  
 2. Delivery time: 3-15 days after the the 30% deposit .  
 3. Payment: 30% T/T in advance,the 70% balance can be paid before  
 4. Period of validity:30 days.  
 5. 2 years