


## 19" Industrial Grade CCTV monitor

Size	Model	Picture	Parameters																						
19.6"	MC190MA	   <p>19寸频</p>  <p>丰富的工业级监视器接口</p> <p>正面简易的按键操作</p>	<table border="1"> <tr> <td><b>Panel</b></td><td>           Size: 19"(high brightness,high resolution)            Display area: 340mm(W)x272mm(H)            Aspect ratio: 4 : 3            Dot Pitch: 0.264mmx0.264mm(H,V)            Resolution: 1280x900            Contrast ratio: 500:1            Brightness: 450cd/m<sup>2</sup>            Response time: 5ms            Viewing angle: 178°/178°            Color: 16.7M            Life span: 50,000(hours)         </td></tr> <tr> <td><b>Exclusive function</b></td><td>           Industrial metal shell,wearable and shockproof, anti-jamming, suitable for different environment, Great Radiation            Can make as digital TV, industrial equipment display, Closed-circuit monitor display, computer display            4D color management and image processing technology            Mult inputs available            High Brightness, Full screen display uniformity            brightness enhancement            Instant digital chroma enhancement,Automatic color correction              DNX (Digital Natural Expression) ,Motion compensation image processing technology;            Long life、low Radiation、Environmental protection;         </td></tr> <tr> <td><b>Interface</b></td><td>           VGA: 15 Pin VGA input            BNC1: BNC input            BNC2: BNC input            BNC OUT: BNC output            HDMI: HDMI interface(1080p/1080i/720p)            YPBPR R/L: chromatic aberration signal &amp; audio signal input            Audio input: PC audio input            Audio output: PC audio output(Digital)            Powr supply: built in AC 100-240V,50/60Hz         </td></tr> <tr> <td><b>Color system</b></td><td>PAL/NTSC/SECAM</td></tr> <tr> <td><b>OSD</b></td><td>multi language</td><td>English,French,Spanish,Polish,Portuguese,Italian,German,Dutch,Russian</td></tr> <tr> <td><b>Working temperature</b></td><td>0°C - 50°C</td></tr> <tr> <td><b>Working Humidity</b></td><td>10-90%</td></tr> <tr> <td><b>Installation</b></td><td>Desktop ,Wall mount,can hang on the ceiling</td></tr> <tr> <td><b>Packing size</b></td><td>5units/carton,external carton size: 410*680*500mm</td></tr> <tr> <td><b>Stand-alone power</b></td><td>&lt; 35W</td></tr> </table>	<b>Panel</b>	Size: 19"(high brightness,high resolution) Display area: 340mm(W)x272mm(H) Aspect ratio: 4 : 3 Dot Pitch: 0.264mmx0.264mm(H,V) Resolution: 1280x900 Contrast ratio: 500:1 Brightness: 450cd/m <sup>2</sup> Response time: 5ms Viewing angle: 178°/178° Color: 16.7M Life span: 50,000(hours)	<b>Exclusive function</b>	Industrial metal shell,wearable and shockproof, anti-jamming, suitable for different environment, Great Radiation Can make as digital TV, industrial equipment display, Closed-circuit monitor display, computer display 4D color management and image processing technology Mult inputs available High Brightness, Full screen display uniformity brightness enhancement Instant digital chroma enhancement,Automatic color correction  DNX (Digital Natural Expression) ,Motion compensation image processing technology; Long life、low Radiation、Environmental protection;	<b>Interface</b>	VGA: 15 Pin VGA input BNC1: BNC input BNC2: BNC input BNC OUT: BNC output HDMI: HDMI interface(1080p/1080i/720p) YPBPR R/L: chromatic aberration signal & audio signal input Audio input: PC audio input Audio output: PC audio output(Digital) Powr supply: built in AC 100-240V,50/60Hz	<b>Color system</b>	PAL/NTSC/SECAM	<b>OSD</b>	multi language	English,French,Spanish,Polish,Portuguese,Italian,German,Dutch,Russian	<b>Working temperature</b>	0°C - 50°C	<b>Working Humidity</b>	10-90%	<b>Installation</b>	Desktop ,Wall mount,can hang on the ceiling	<b>Packing size</b>	5units/carton,external carton size: 410*680*500mm	<b>Stand-alone power</b>	< 35W	
<b>Panel</b>	Size: 19"(high brightness,high resolution) Display area: 340mm(W)x272mm(H) Aspect ratio: 4 : 3 Dot Pitch: 0.264mmx0.264mm(H,V) Resolution: 1280x900 Contrast ratio: 500:1 Brightness: 450cd/m <sup>2</sup> Response time: 5ms Viewing angle: 178°/178° Color: 16.7M Life span: 50,000(hours)																								
<b>Exclusive function</b>	Industrial metal shell,wearable and shockproof, anti-jamming, suitable for different environment, Great Radiation Can make as digital TV, industrial equipment display, Closed-circuit monitor display, computer display 4D color management and image processing technology Mult inputs available High Brightness, Full screen display uniformity brightness enhancement Instant digital chroma enhancement,Automatic color correction  DNX (Digital Natural Expression) ,Motion compensation image processing technology; Long life、low Radiation、Environmental protection;																								
<b>Interface</b>	VGA: 15 Pin VGA input BNC1: BNC input BNC2: BNC input BNC OUT: BNC output HDMI: HDMI interface(1080p/1080i/720p) YPBPR R/L: chromatic aberration signal & audio signal input Audio input: PC audio input Audio output: PC audio output(Digital) Powr supply: built in AC 100-240V,50/60Hz																								
<b>Color system</b>	PAL/NTSC/SECAM																								
<b>OSD</b>	multi language	English,French,Spanish,Polish,Portuguese,Italian,German,Dutch,Russian																							
<b>Working temperature</b>	0°C - 50°C																								
<b>Working Humidity</b>	10-90%																								
<b>Installation</b>	Desktop ,Wall mount,can hang on the ceiling																								
<b>Packing size</b>	5units/carton,external carton size: 410*680*500mm																								
<b>Stand-alone power</b>	< 35W																								