



LCD specifications	Model	MC351
	Size	3.5 inch TFT lcd
	Screen ratio	4:3
	Maximum resolution	320x240
	Contrast	300:1
	Brightness (cd/m ²)	200cd/m ²
	Response Time (ms)	5ms
	Perspective	96 * 54(H/V)
Life (hrs)	50,000(hrs)	
Panel Color	Black	
Definition	3D digital comb filter (PAL / NTSC)	
	3D digital noise reduction	
	HD high-definition signals	
	Progressive scan	
	10-bit LCD panel driver a better over-color, smooth vivid	
	WCG-CCFL backlight color	
	Dual-screen function	
Video Standard	PAL/NTSC	auto-identification
Support of the resolution	320x240	
Amplifier / Power	2 x 16 ohms / 3W	
Power machine	Status of work: 35W (maximum); standby: 1W	
Port	2*RCA (AV) INPUTS	
Camera	Option	
Menu Language	English Chinese; (to be available in multiple languages)	
Temperature / humidity	0 °C ~ 50 °C / 20% ~ 80% (no condensation)	
Storage temperature / humidity	-10 °C ~ 60 °C / 5 - 95% (no condensation)	
Appendix	A Manual	
	A warranty card	
	AC power cord of a	
	Wall stent (optional)	
	A power adapter (DC12V)	