



LCD specifications	Size	4.3 inch TFT lcd
	Screen ratio	16:09
	Maximum resolution	640x480
	Contrast	300:1
	Brightness (cd/m2)	200cd/m ²
	Response Time (ms)	5ms
	Perspective	96 * 54(H/V)
Life (hrs)	50,000(hrs)	
Color	Black or White	
Definition	3D digital comb filter (PAL / NTSC)	
	3D digital noise reduction	
	HD high-definition signals	
	Progressive scan	
	10-bit LCD panel driver a better over-color, smooth vivid	
	WCG-CCFL backlight color	
Video Standard	PAL/NTSC	auto-identification
Inputs	2AV inputs & DC input	
Amplifier / Power	2 x 16 ohms / 3W	
Power machine	Status of work: 35W (maximum); standby: 1W	
Button panel	UP,Down,Menu,Power,Left,Right;Mode/ Auto,Menu,Power,Left,Right;Mode	
Menu Language	English Chinese; (to be available in multiple languages)	
	Custom	
Product Architecture	Strong metal chassis, anti-static, anti-magnetic field, strong anti-interference	
Temperature / humidity	0 °C ~ 50 °C / 20% ~ 80% (no condensation)	
Storage temperature / humidity	-10 °C ~ 60 °C / 5 - 95% (no condensation)	
Appendix	A Manual	
	A warranty card	
	AC power cord of a	
	Wall stent (optional)	
	A power adapter (DC12V-24V)	

Remark:

1. Trade Term: EXW Shenzhen
2. MOQ:1000PCs (small trial order also acceptable)
3. Delivery time: 7-10 days after the the 30% deposit .
4. Payment: 30% T/T in advance,the 70% balance can be paid before shipment.
5. Period of validity:15 days since 2018.9.10
6. Warranty: 2 Years Guarantee