



SPEC	Size	24"	
	Resolution	1920*1080	
	Refresh Rate	75 / 144Hz	
	Panel Type	VA	
	Active Area	521.3952 (H) x 293.2848(V)	
	Dot Pitch	0.27156 (H) x 0.27156(W)	
	Curvature	1500R	
	Aspect ratio	16:9	
	Backlight	LED	
	Brightness	250cd/m ²	
	Contrast Ratio	3000:1	
	Color Temperature	default:7500K 6500/7500/9300	
	Number of colors	16.7M	
	Color Gamut	NTSC 72%	
	View Angle	178°/178° (H/V)	
	Response Time	3ms	
	Kendington Lock	YES	
	VESA Mounting	100*100mm	
	Video	VGA+HDMI	
	NOTE	VGA: 1920*1080 60Hz HDMI: 1920*1080 75Hz	
	Speaker	Optional	
	Audio Ports	IN or OUT	
PSU	Input	DC:12V3A	
	Type	Adapter	
	Power Consumption	Typ.:26W,Max:32W STB ≤0.5W	
Structure	Stand	Plastic	
	Base	Right/left rotatable 15°	
	Colors		Front: Black(Red)
			Back cover: Black
			Stand: Black
			Base: Black
	Size	W/ Base	537.15*315.97*82.16mm
		W/O Base	537.15*411.82*210.00mm
Package		612.0*136.0*410.0mm	
Weight	N.W	3.6kg	
	G.W	4.9kg	
	Tilt	Forerake 5° , Fadeaway 15°	
Panel Control	Control Way	5 Keys	
	Language Menu	12 languages max	
Environment	Storage Temp.	-20°C~60°C	
	Working Temp.	0°C~40°C	
	Working Humidity	10~90%RH	
	Altitude	≤5000m	
Key Functions		1. Color Temp. (cold/warm/user)	
		2. Low blue light eyeprotect technology	
		3. Five key control	
		4. DCR	
		5. Multi-language Memu	
		7.FPS/RTS Gaming mode switch	
Quantity	20'GP	600pcs	
	40'GP	1260pcs	
	40'HQ	1386pcs	