



SPC	size		31.5"
	Resolution		1920X1080
	Refresh rate		165 / 240 Hz
	Panel type		VA
	Active Area		698.4mm(H)X392.85mm(V)
	Dot Pitch		0.36375(H) x 0.36375(V)mm
	Curvature		R1500
	Aspect ratio		16:9
	Backlight		LED
	Brightness		MAX:300cd/M ²
	Contrast Ratio		1000:1
	Color Temp. default		default:7500K 6500/7500/9300
	Number of colors		16.7M
	Color Gamut		NTSC 85%
	Viewing angle		178/178 (H/V)
	Response time		1ms(GTG)
	Port		VGA+DVI+HDMI+DP+audio out
Note		VGA: 1920*1080 60HZ DVI: 1920*1080 60HZ HDMI: 1920*1080 144HZ/165HZ DP: 1920*1080 144HZ/165HZ	
Speakers		Optional	
Audio		AUDIO OUT or PC AUDIO IN	
PSU	Input		100-240AC 50/60HZ
	Type		Built in
	Power Consumption		typical:45W,Max:55W STB ≤0.5W
Other	Colors		Front: BLACK Back cover: BLACK Back cover light: multicolor Stand: RED+BLACK Base: BLACK
	Size	W/ Base	714.4mm*106.2mm*424mm
		W/O Base	714.4mm*283mm*567.5mm
		Pacakge	794*189*591mm
	Weight	N.W	8.2KG
		G.W	10.2KG
	Stand		Optional
	Tilt		Forerake 5° , Fadeaway 15°
	Kendington Lock		YES
	VESA Mounting		100*100mm
	Rotating angles		0-90°
High Adjustable Arm		130mm	
Swivel		25°/25°	
Panel Control	Control Way		Key OSD
	Language Menu		6 languages max
Environment	Storage Temp.		-20°C~60°C
	Working Temp.		0°C~40°C
	Working Humidity		10~90%RH
	Altitude		≤5000m
Key Functions		1. Color Temp. (cold/warm/user) 2. Low blue color control ; 3. Five key control ; 4. DCR; 5. Multi-language Memu ; 6. FreeSync ; 7.FPS/RTS Gaming mode switch	
Accessories		User Manual , Power Adapter and Cable , DP Cable	
Volume	with Pallet	20GP/PCS	230
		40GP/PCS	483
		40HQ/PCS	588
	without pallets	20GP/PCS	294
		40GP/PCS	588
		40HQ/PCS	672
MOQ for OEM/PCS		500	

Remark :

- Trade Term: FOB shenzhen based on MOQ
- MOQ: 500pcs (small trial order also acceptable by EXW price)
- Delivery time: 3-15 days after the the 30% deposit .
- Payment: 30% T/T in advance, the 70% balance can be paid before shipment.
- Period of validity: 15 days.