





	T		I
	CPU		RK3588 Quad core cortex A55+Quad core cortex A76
System	RAM		8GB
System	ROM		128GB
	Operating system		Android 12
Display	Panel		27"inch
	Screen type		IPS
	Resolution		1920*1080
	Chromatic number		16.7M Colors
	Color gamut		72% NTSC
	Viewing angle		R/L 89/89, U/D 89/89
	Display mode		Normally black
	Contrast ratio	+	.1000:1
	Response time (GtG)		6ms
	Backlight		LED
	Luminance		450cdm2
	Aspect Ratio		1.16: 9
Touch Wireless network IO/Interface	Touch type		In cell touch
	Touch points		10-Point capacitive touch
	Touch interface		HID-USB
	WiFi		IEEE 802.11b/g/n/a/ac/ax
	Bluetooth		Bluetooth 5.3
	Type C		Full Function (Except for charging function)
	DP in		DP IN function, Compatible with PD fast charge output, support 5V/3A,9V/3A,12V/3A,15/3A output
	USB		USB 3.0 HOST
	HDMI IN		Support 800*600,1024*768,1280*720,1280*800,1280*1024,1366*768,1600*900,1920*1080,3840*2160, etc
	AC power input		Socket,AC voltage 100-240V input
	Rocker switch		Control the motherboard battery switch
	Storage box		*3
	Video format		MPEG-1,MPEG-2,MPEG-4,H.265,H.264,H.263,VC-1,VP8,VP9,MVC,AV1, etc., support up to 8K@60fps
Media playback			
Media playback	Audio format		MP3/WMA/AAC/WAV/OGG, etc
Media playback			
Media playback	Photo		MP3/VMA/AAC/WAV/OGG, etc JPEG/PNG/GIF, etc Warm Grev
Media playback	Photo Product Color	×3 (front)	JPEG/PNG/GIF,etc Warm Grey
Media playback	Photo Product Color Key	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Yolume+
Media playback	Photo Product Color Key Gravity Sensor	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation
Media playback	Photo Product Color Key Gravity Sensor Horn	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2
Media playback	Photo Product Color Key Gravity Sensor Horn Microphone	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+(Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω /10W*2, woofer 2.5inch 4Ω /10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation
	Photo Product Color Key Gravity Sensor Horn	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+/Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English
Media playback Other	Photo Product Color Key Gravity Sensor Horn Microphone	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+(Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω /10W*2, woofer 2.5inch 4Ω /10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+/Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy	×3 (front)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+(Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15%
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication		JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy	×3 (front) Three color LED light	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2. woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15%
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication		JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front)		JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2. woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual 0SD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation
Other	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type		JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the light; Shutdown and hibernation 18650 type lithium-ion battery
	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity		JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh
Other	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type		JPEG/PNG/GIF,etc Warm Grey Power/Volume+(Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2. woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC. FCC. CE. CB. DOE. UL. ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-8H [Comprehensive Evaluation]
Other	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity	Three color LED light	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3
Other	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity	Three color LED light Tilt (Forward-Backward)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees
Other Battery pack	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance	Three color LED light Tilt (Forward-Backward) Rotation (clockwise)	JPEG/PNG/GIF,etc
Other Battery pack	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance	Three color LED light Tilt (Forward-Backward)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H (Comprehensive Evaluation) For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0-90° 200mm
Other Battery pack	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance	Three color LED light Tilt (Forward-Backward) Rotation (clockwise)	JPEG/PNG/GIF,etc
Other Battery pack Structure	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature	Three color LED light Tilt (Forward-Backward) Rotation (clockwise)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0-90° 200mm 0°C-45°C
Other Battery pack	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Storage Temperature	Three color LED light Tilt (Forward-Backward) Rotation (clockwise)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode, Forward litt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0—90° 200mm 0°C~45°C -20°C~60°C
Other Battery pack Structure	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Storage Temperature Operation Humidity	Three color LED light Tilt (Forward-Backward) Rotation (clockwise)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2. woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC. FCC. CE. CB. DOE. UL. ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level > 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-8H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0-90" 200mm 0°-45° 20-60%RH
Other Battery pack Structure	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Storage Temperature Operation Humidity	Three color LED light Tilt (Forward-Backward) Rotation (clockwise) Lifting (Center Distance)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+\(Volume-\) Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0−90° 200mm 0°C−45°C 20°C−80%RH 10~95%RH
Other Battery pack Structure	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Storage Temperature Operation Humidity Storage Humidity Storage Humidity Storage Humidity Storage Torperature 1.5 me	Three color LED light Tilt (Forward-Backward) Rotation (clockwise) Lifting (Center Distance)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Battery level > 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H Comprehensive Evaluation For Landscape Mode: Forward lit 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0−90* 200mm 0°C−45°C -20°C−60°C 20-80%RH 10−95%RH 11-95%RH
Other Battery pack Structure Environment	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Storage Temperature Operation Humidity Storage Humidity AC power cord length 1.5 me Dual TYPE-C cable length 0.5 me	Three color LED light Tilt (Forward-Backward) Rotation (clockwise) Lifting (Center Distance)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+\(Volume-\) Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0−90° 200mm 0°C−45°C 20°C−80%RH 10~95%RH
Other Battery pack Structure	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Operation Humidity Storage Humidity AC power cord length 1.5 me Dual TYPE-C cable length 0.1	Three color LED light Tilt (Forward-Backward) Rotation (clockwise) Lifting (Center Distance)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 ° rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Flashing during AC charging, always on when fully charged Red light; Battery level ≤ 15% Turn off the light; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H [Comprehensive Evaluation] For Landscape Mode: Forward tilt 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0−90° 200mm 0℃−45℃ -20℃−60℃ -20℃−80%RH 10−95%RH *1 *1 *1 *1 *1
Other Battery pack Structure Environment	Photo Product Color Key Gravity Sensor Horn Microphone OSD Language Closure dormancy Authentication LED light (front) Battery type Battery pack capacity Endurance Function Operation Temperature Storage Temperature Operation Humidity Storage Humidity AC power cord length 1.5 me Dual TYPE-C cable length 0.5 me	Three color LED light Tilt (Forward-Backward) Rotation (clockwise) Lifting (Center Distance)	JPEG/PNG/GIF,etc Warm Grey Power/Volume+Volume- Supports 90 * rotation tweeter 0.75inch 4Ω/10W*2, woofer 2.5inch 4Ω/10W*2 Standard built-in 4 microphones, supporting noise reduction and echo cancellation Multilingual OSD operation in Chinese and English Supports lid closure sleep, lid opening wake-up/lid opening startup CCC, FCC, CE, CB, DOE, UL, ERP Blue light; Battery level > 15% Green light; Battery level > 15% Turn off the lights; Shutdown and hibernation 18650 type lithium-ion battery 14.4V/6800mAh 5-6H Comprehensive Evaluation For Landscape Mode: Forward lit 3 degrees, backward tilt 90 degrees; For Portrait Mode: Forward tilt 3 degrees, backward tilt 40 degrees 0−90* 200mm 0°C−45°C -20°C−60°C 20-80%RH 10−95%RH 11-95%RH

Drawing











