

Item No.:	MO1701-Q		
Description:	17 inch Industrial Metal Frame Touch Screen Monitor		
			
Specification			
General			
Series	Water-proof and Open frame		
LCD Type	17" TFT-LCD		
Video Input	VGA and DVI , HDMI - optional		
OSD controls	Allow on-screen adjustments of Brightness, Contrast Ratio, Auto-Languages, Function, Reset		
Power Supply	Type: External brick		
	Input (line) voltage: 100-240 VAC, 50-60 Hz		
	Output voltage/current: 12V 3A		
Mount Interface	1)VESA 75*75 or 100*100 mm		
	2)Mount bracket, horizontal or vertical		
LCD Specification			
Resolution	1280x880 @75Hz		
Dot Pitch(mm)	0.297× 0.297		
Nominal Input Voltage VDD	+3.3V(Typ)		
Viewing angle (v/h)	80°/80°		
Contrast	1000:1		
Luminance(cd/m2)	350cd/m2 （1000cd/m2 option）		
Response Time(Rising/Falling)	5ms/6ms		
Support Color	16.2M		
Backlight MTBF(hr)	50000		
Touchscreen Specification			

Resolution	10points touch
Touch Life Cycle	10 millions
Touch Response time	5ms
Touch System Interface	USB interface
Power consumption	+5V@80mA
External AC Power Adapter	
Output	DC 12V /4A
Input	100-240 VAC, 50-60 Hz
MTBF	50000 hr at 25°C
Environment	
Operating Temp.	0~50°C
Storage Temp.	-20~60°C
Operating RH:	20%~80%
Storage RH:	10%~90%
Components	
USB Cable 180cm*1 Pcs, VGA Cable 180cm*1 Pcs, Power Cord with Switching Adapter *1 Pcs, HDMI Cable 180 cm*1 Pcs	

[illegible]

[illegible]